

Buccaneer Excavator

The Bomford Buccaneer Excavator is suitable for use with excavators from 7 to 30 tonnes.

There are 4 ranges available:

SDH Range - With swinging hammers and 360° movement suited to mulch brush up to 200mm diameter.

SDFH Range - As above but suited to mulch brush up to 300mm diameter.

HDH Range - with fixed hammers, with tungsten carbide teeth suited to mulch brush up to 200mm diameter.

HDFH Range - As above but suited to mulch brush up to 300mm diameter.

Key Features

- Working with oil pressure ranges of 200 to 260psi
- Working with oil flows between 80 to 205 L/min
- Weight options from 912kg up to 1,902kg



Want to know more about the Buccaneer Excavator?

Scan the QR code to the left with a smart phone or tablet and compatible app to instantly view the page.

Alternatively visit: <http://www.bomford-turner.com/forestry/buccaneer-excavator/>



Protection

Double rows of heavy chains and adjustable skids.



Fixed hammers

Options available. Suitable for managing wooded areas.



Heavy duty drive

7 belt drive system.

Product Specification

SDH Range	SDH130	SDH150	SDH180
Working width	1300mm / 4'3"	1500mm / 4'11"	1800mm / 5'10"
Transport width	1500mm / 4'11"	1750mm / 5'8"	2000mm / 6'6"
Cutting Diameter	200mm	200mm	200mm
Number of Hammers	20	20	20
Number of Belts	7	7	7
Hammer Type	Swing	Swing	Swing
Weight	957kg / 2110lbs	1013kg / 2233lbs	1070kg / 2359lbs
Oil flow L/min	80-120L / 21-32 USG	80-120L / 21-32 USG	80-120L / 21-32 USG
Oil pressure (Bar)	200-260	200-260	200-260

HDH Range	HDH140	HDH180	HDH200
Working width	1400mm / 4'7"	1800mm / 5'10"	2000mm / 6'6"
Transport width	1700mm / 5'6"	2100mm / 6'10"	2300mm / 7'6"
Cutting Diameter	250mm	250mm	250mm
Number of Hammers	12	16	20
Number of Belts	7	7	7
Hammer Type	Swing	Swing	Swing
Weight	1658kg / 3655lbs	1815kg / 4001lbs	1902kg / 4193lbs
Oil flow L/min	155L / 41 USG	175L / 46 USG	205L / 54 USG
Oil pressure (Bar)	200-260	200-260	200-260

SDFH Range	SDFH130	SDFH150	SDFH180
Working width	1300mm / 4'3"	1500mm / 4'11"	1800mm / 5'10"
Transport width	1500mm / 4'11"	1750mm / 5'8"	2000mm / 6'6"
Cutting Diameter	200mm	200mm	200mm
Number of Hammers	22	26	30
Number of Belts	7	7	7
Hammer Type	Fixed	Fixed	Fixed
Weight	912kg / 2011lbs	960kg / 2116lbs	1018kg / 2244lbs
Oil flow L/min	80-120L / 21-32 USG	80-120L / 21-32 USG	80-120L / 21-32 USG
Oil pressure (Bar)	200-260	200-260	200-260

HDFH Range	HDFH140	HDFH180	HDFH200
Working width	1400mm / 4'7"	1800mm / 5'10"	2000mm / 6'6"
Transport width	1700mm / 5'6"	2100mm / 6'10"	2300mm / 7'6"
Cutting Diameter	250mm	250mm	250mm
Number of Hammers	22	26	30
Number of Belts	7	7	7
Hammer Type	Fixed	Fixed	Fixed
Weight	1517kg / 3344lbs	1680kg / 3704lbs	1760kg / 3880lbs
Oil flow L/min	155L / 41 USG	175L / 46 USG	205L / 54 USG
Oil pressure (Bar)	200-260	200-260	200-260



Versatile cutting

From green waste and vegetation to wooded areas, the Buccaneer Excavator is capable of clearing any environment.

Used in conjunction with the Excavators slewing action large areas can be cleared quickly leaving a chipped or mulched finish dependent upon hammer choice.