

Turbo Mower

The Turbo Mower Elite, Euro, Open and Pro range offers operators a huge choice of cutting widths at very cost effective prices.

A well designed and constructed range, the Turbo Mower is built with durability and ease-of-use in mind – a low maintenance machine that is simple to operate.

Key Features

- Choice of cutting widths available
- Front mount options
- 1.3 and 1.5 manual offset
- Hydraulic offset standard on 1.9m and above
- Standard fitted roller and side skids
- Cat II three point linkage mounted
- Over run slip clutch protected
- Now with a 2 year warranty



Want to know more about the Turbo Mower range?

Scan the QR code to the left with a smart phone or tablet and compatible app to instantly view the page.

Alternatively visit: <http://www.bomford-turner.com/landscape/flail-mowers-and-toppers/turbo-mower/>



Adjustable guards

On some models the rear hood can be opened.



Compact models

Machines for tractors over 800kg and above 30HP.



Twin head stock

Front and rear mount options available.

Product Specification

● Standard ○ Optional — Not Available

Turbo Mower	ELITE 130	ELITE 150	ELITE 190	ELITE 225	ELITE 245	ELITE 270	OFFSET 160	OFFSET 225
Working Width	1.3m / 4'3"	1.45m / 4'9"	1.9m / 6'4"	2.26m / 7'5"	2.42m / 8'	2.72m / 8'10"	1.6m / 5'3"	2.25m / 7'4"
Overall Width	1.47m / 4'10"	1.63m / 5'4"	2.1m / 6'10"	2.45m / 8'	2.6m / 8'6"	2.9m / 9'6"	1.8m / 6'	2.45m / 8'
Weight	213kg / 469lbs	237kg / 522lbs	451kg / 994lbs	554kg / 1221lbs	596kg / 1313lbs	632kg / 1393lbs	665kg / 1466lbs	775kg / 1709lbs
Hydraulic Offset	—	—	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated
Fully offset left of centre	—	—	400mm / 15 1/2"	400mm / 15 1/2"	400mm / 15 1/2"	400mm / 15 1/2"	2700mm / 9'	3350mm / 11'
PTO speed	540	540	540	540	540	1000	540	540
Front mount	—	—	—	—	—	—	—	—
No. of Flails (Whale Tail)	18	20	24	28	30	34	20	28
Power requirements	30-37hp	35-40hp	45-60hp	55-75hp	65-90hp	75-100hp	47-60hp	80-117hp
Cutting height	32-111mm 1 1/4" - 4 1/2"	32-111mm 1 1/4" - 4 1/2"	32-111mm 1 1/4" - 4 1/2"	32-111mm 1 1/4" - 4 1/2"	32-111mm 1 1/4" - 4 1/2"	32-111mm 1 1/4" - 4 1/2"	30-80mm 1 1/4" - 3 1/4"	30-80mm 1 1/4" - 3 1/4"
Roller size	114mm / 4 1/2"	114mm / 4 1/2"	140mm / 5 1/2"	140mm / 5 1/2"	140mm / 5 1/2"	140mm / 5 1/2"	140mm / 5 1/2"	140mm / 5 1/2"

Turbo Mower	EURO 250	EURO 280	OPEN 250	OPEN 280	PRO 250	PRO 270	PRO 300
Working Width	2.5m / 8'3"	2.8m / 9'2"	2.44m / 8'	2.77m / 9'1"	2.45m / 8'	2.70m / 8'10"	3.00m / 9'10"
Overall Width	2.67m / 8'9"	3m / 9'10"	2.67m / 8'9"	3m / 9'10"	2.73m / 8'11"	2.98m / 9'9"	3.28m / 10'9"
Weight	867kg / 1911lbs	939kg / 2070lbs	859kg / 1893lbs	928kg / 2045lbs	1210kg / 2667lbs	1284kg / 2830lbs	1390kg / 3064lbs
Hydraulic Offset	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated
Fully offset left of centre	500mm / 19 1/2"	500mm / 19 1/2"	500mm / 19 1/2"	500mm / 19 1/2"	400mm / 15 1/2"	400mm / 15 1/2"	400mm / 15 1/2"
PTO speed	1000	1000	1000	1000	1000	1000	1000
Front mount	●	●	—	—	●	●	●
No. of Flails (Whale Tail)	28	32	28	32	20	24	26
Power requirements	65-110hp	75-110hp	65-100hp	75-110hp	68-80hp	80-120hp	95-135hp
Cutting height	43-88mm 1 1/4" - 3 1/2"	43-88mm 1 1/4" - 3 1/2"	32-111mm 1 1/4" - 4 1/2"	32-111mm 1 1/4" - 4 1/2"	45-157mm 1 1/4" - 6 1/4"	45-157mm 1 1/4" - 6 1/4"	45-157mm 1 1/4" - 6 1/4"
Roller size	170mm / 6 3/4"	170mm / 6 3/4"	170mm / 6 3/4"	170mm / 6 3/4"	220 / 8 1/2"	220 / 8 1/2"	220 / 8 1/2"



Offset mower

Capable of being fully offset and cutting within the width of the tractor. Cutting angles vertical 90° and down 65°.

