

# Wren

Compact yet powerful, the Wren is the latest addition to the range of arm mowers from Bomford Turner and offers an excellent entry-level solution to your landscaping maintenance needs.

Fitted with twin pumps and fully independent hydraulics, the Wren can operate a range of different attachments.

## Key Features

- 3.0m or 3.5m reach
- Left or Right hand cutting option
- Cable control
- Front or rear mount option
- Mechanical breakout
- Cutter bar option



### Want to know more about the Wren range?

Scan the QR code to the left with a smart phone or tablet and compatible app to instantly view the page.

Alternatively visit: [www.bomford-turner.com/landscape/arm-mowers/wren/](http://www.bomford-turner.com/landscape/arm-mowers/wren/)



## Product Specification

● Standard ○ Optional — Not Available

Wren	3.0m (9'10")	3.5m (11'5")
<b>Tractor requirements</b>		
Minimum horse power	15hp	15hp
Minimum weight	800kg/1764lbs	800kg/1764lbs
<b>Base unit mounting options</b>		
Front mount	●	●
Mid-mount	—	—
Rear mount	●	●
Three point linkage (CAT II)	●	●
Axle bracket	—	—
<b>Overall machine parameters</b>		
Machine weight with head and oil	192kg/423lbs	201kg/448lbs
Capacity of oil tank	60L / 15.6USG	60L / 15.6USG
<b>Controls</b>		
Cable control (CC)	●	●
Electronic proportional control (EPP)	—	—
Intelligent control system (ICS)	—	—
Low pressure hydraulics (LPH)	—	—
Cable rotor reverse	●	●
Electronic rotor reverse	—	—
<b>Hydraulic System</b>		
System capability	30hp	30hp
Pump flow rate	50L / 13.2USG	50L / 13.2USG
Pump type (Gear / Piston / Helical)	Gear	Gear
Pump arrangement (Twin / Tandem InLine)	Twin	Twin
Independent hydraulics	●	●
Oil cooler	—	—

Wren	3.0m (9'10")	3.5m (11'5")
<b>Arm features and main frame</b>		
Telescopic arm	—	—
Telescopic arm stroke	—	—
Power slew	—	—
Power slew angle	—	—
Gravity breakout	○	○
Hydraulic breakout	—	—
Armfloat - manual	—	—
Armfloat - electronic	—	—
Headfloat - manual	—	—
Headfloat - electronic	—	—
Left hand cutting	—	—
Right hand cutting	○	○
Left and right hand cutting	○	○
<b>Cutting heads</b>		
0.6m Flailhead	●	●
0.8m Flailhead	○	○
Rotary Heads	—	—
1.2m and 1.5m cutterbars	○	○
Ditch Cleaner	—	—

### Cable rotor reverse

Fitted as standard. Ideal for cutting both brush and grass.

### Fully independent hydraulics

For continuous use. Twin pumps with separate oil tank.




### Gravity breakout system

For protecting drive and machine during operation.

## Working Reach

Head used for calcs: **0.6m Flail Head**

	Wren 3.0m (9'10")	Wren 3.5m (11'5")
<b>A</b>	2.8m / 9'2"	3.3m / 10'10"
<b>B</b>	2.8m / 9'2"	3.3m / 10'10"
<b>C</b>	1.7m / 5'7"	2.2m / 7'3"
<b>D</b>	1.55m / 5'1"	1.8m / 5'11"
<b>E</b>	3.0m / 9'11"	3.5m / 11'6"
<b>X</b>	1.0m / 3'3"	1.0m / 3'3"
<b>Y</b>	0.7m / 2'4"	0.7m / 2'4"



### Multi-purpose flails

For grass and hedges.

